Dillon



Dillon

Content:

100% Polyurethane

Backing:

70% Polyester, 30% Cotton

Finish:

Antimicrobial -- silver based ion technology

Weight:

20.32 oz. per linear yard

Width:

54"

Environmental Benefit:

PVC Free

Phthalate - compliant CPSC sec. 108 Lead - compliant CPSC sec. 101

Abrasion:

Heavy Duty - Exceeds 200,000 Cycles

(Wyzenbeek - #8 Cotton Duck Abradant) (ASTM D4157)

Light Fastness:

Class 4/100 hrs. min. (AATCC16A)

Color Fastness:

Class 5 (ASTM D3597, AATCC 8) Wet Class 5 (ASTM D3597, AATCC 8) Dry

Physical Properties:

Class 5 (ASTM D3511) Brush Pill

130 lbs. warp, 120 lbs. weft (ASTM D5034) Breaking Strength 61 lbs. warp, 81 lbs. weft (ASTM D4034) Seam Slippage

ISO 1419 - passes 5 weeks

Passes:

California Tech. Bulletin #117 - 2013

UFAC Class I NFPA 260 Class I MVSS 302 Pass

Cleanability:

WS - Both water and solvent based solutions Bleach Cleanable - 5:1 water/bleach solution

This fabric is made in China.

GRADE B 2016

Please refer to the RFM pricing guide for product information, specifications, warranties and options.

RFM seating

619 S.W. Wood Street | Hillsboro, OR 97123

503.648.6121 | 800.447.5542 | Fax: 800.734.6377 | www.rfmseating.com